



## DESCRIPTION

Each 3D lava stone furniture is handcrafted by experienced professionals who are keen on details. There are plenty of options to choose from among our 3D pieces, a collection of reliable products that offer durability & support, visual appeal, and quality craftsmanship. The tiles are glazed one by one, thus meaning that you will get complete say with regards to colors, glazing effects and color matching.

3D tiles are suitable both for desk and wall cladding so you can create aesthetic references between the design of the counter and the surrounding environment. Our specialized team can assist through the whole project, ensuring that you can take advantage of the incredible versatility of our 3D pieces, and get the best tailor made result.

## TECHNICAL DETAILS

- Wide range of colours
- High resistance to chemicals
- High resistance to all weather conditions
- Nonporous: Waterproof
- Easy to clean

## DISCLAIMER

Lava Stone is a natural product and could present itself with slight imperfections that are not homogeneous. The glazing and decorating of the stone is done by hand and the firing process takes place at temperatures of approx. 10000°C. Slight imperfections or variation in shade certify the handmade nature of this product.

Glazed lava samples may vary in pigment, and the glaze could present some fine cracks, particularly in surfaces which have been cut from larger slabs. In certain cases we send out control samples in the desired thickness to ensure a similar finish at the time of order.

## PRODUCT DETAILS

Product Code	: <b>BT-TG-01</b>
Product Name	: <b>Tango</b>
Category	: <b>Lava Stone</b>
Brand	: <b>Ranieri Lava Stone</b>
Origin	: <b>Italy</b>

## SIZE

Size	<b>400B: H 400 x W 150 mm</b>
	<b>600B: H 600 x W 150 mm</b>
	<b>800B: H 800 x W 150 mm</b>

Thickness	: <b>20 mm</b>
-----------	----------------

## SPECIFICATIONS

Material	: <b>Lava Stone</b>
Collection	: <b>3D Bar Tiles</b>
Finish	: <b>Various</b>

## USEFUL DATA

Suitable for	: <b>Commercial   Residential</b>
Installation method	: <b>Tile adhesive</b>
Applications	: <b>Wall   Indoor   Outdoor</b>
Warranty	: <b>10 Years</b>
Cutting Tolerance	: <b>± 1 mm</b>

## INSTALLATION

We suggest a 2 mm epoxy grouting between each tile. In this case the tiles will be glazed only on the front. No glazing will be applied to the side edges. To be installed without grouting, all the edges must be glazed.

Special pieces for corner and curved surfaces on request.

It is the responsibility of the specifier to source any profiling to use between tiles. We do not supply nor quote for metal or brass profiling.